

RRM VB26

SKU: RRM B1901 48.48



SPECIFICATIONS

DIMENSIONS

External Dimensions (L/W/H)
Internal Dimensions (L/W/H)

1,212.9 / 1,212.9 / 724 (mm) 1,108 / 1,108 / 594.6 (mm) 47.75 / 47.75 / 28.5 (in) 43.625 / 43.625 / 23.438 (in)

LOGISTICS

Load Capacity	1,300 lbs
Volume Capacity	49,603 cu.in./812.85 (liters)
Tare Weight	76 lbs
Maximum Stack Weight	12,000 lbs (long term, ambient) 13,000 lbs [short term (<1 month), ambient] 15,000 lbs [long term cold storage (0°F to 35°F)]
Fork Lift Entry	2-Way: 3" opening with patented integral slide-entry
Foot Design	Two full-length feet with forklift opening; positive interlocking foot design

MATERIAL (If Applicable)

Color: Gray

Material: PP, U.V. Stabilized











RRM VB26

SKU: RRM B1901 48.48









- High-pressure injection molded
- FDA approved
- Option include: Customer ID with RFID tags or foil embossing
- 100% stack compatibility
- Lightweight construction and nonporous surface.
- Ventilation slots on the sides and base to reduce heat absorption and cooling costs, providing quicker drying and degreening.
- Easy to sanitize